

# PL 801

<b>TIRE SIZE</b>	<b>7.00 - 15</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊗ BIAS
<b>MACHINERY</b>	ERNTMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE / ROTORSCHWADER / GABELSTAPLER / ERNTMASCHINE / GABELSTAPLER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	206	<b>RIM REC</b>	6.0
<b>OD (MM)</b>	775	<b>RIM ALT</b>	5.50 BD ; 5.5
<b>SLR (MM)</b>	0	<b>PR</b>	12
<b>RC (MM)</b>	0		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	8.60	9.00
25 LOAD WHEEL	2835	-
25 STEER WHEEL	2395	-
10 OTHER VEHICLES	2395	-
25 OTHER VEHICLES	1760	-
STATIC SIDE LOADER	-	3865

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.