

# AGRIMAX V-FLECTO

|                  |                              |
|------------------|------------------------------|
| <b>TYRE SIZE</b> | <b>VF 650/65 R 42 NRO</b>    |
| <b>UM</b>        | IS STANDARD                  |
| <b>MACHINERY</b> | HIGH-POWER TRACTOR / TRACTOR |
| <b>VERSION</b>   | STANDARD                     |
| <b>TL/TT</b>     | TL                           |
| <b>LI/SS</b>     | 174 D                        |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 650  | <b>RIM REC</b> | DW 23 B         |
| <b>OD (MM)</b>  | 1913 | <b>RIM ALT</b> | DW 21 B         |
| <b>SLR (MM)</b> | 852  | <b>ECE</b>     | E11-106R-005713 |
| <b>RC (MM)</b>  | 5773 | <b>SRI</b>     | 925             |

## LOAD CAPACITY (KG/TYRE)

| KM/H / BAR                     | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  |
|--------------------------------|------|------|------|------|------|------|------|
| 70                             | 3105 | 3590 | 4080 | 4630 | 5055 | 5485 | 6095 |
| FROM 65 TO 40                  | 3415 | 3950 | 4485 | 5090 | 5560 | 6030 | 6700 |
| 30                             | 3480 | 4025 | 4570 | 5190 | 5670 | 6150 | 6830 |
| 20                             | 3350 | 4105 | 4660 | 5290 | 5780 | 6270 | 6965 |
| 10                             | 3755 | 4345 | 4930 | 5595 | 6115 | 6630 | 7370 |
| *UPTO 10 CYC WITH FRONT LOADER | 4780 | 5530 | 6275 | 7125 | 7780 | 8440 | 9380 |
| 10HT                           | 3480 | 4025 | 4570 | 5190 | 5670 | 6150 | 6830 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.