


# MULTIMAX MP 522



<b>TIRE SIZE</b>	500/70 R 24 IND
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	COMPACT LOADER / TELEHANDLER / COMPACT LOADER / TELEHANDLER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	164 A8/B

## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	503	<b>RIM REC</b>	DW 16 L
<b>OD (MM)</b>	1310	<b>RIM ALT</b>	DW 15 L; DW 18 L
<b>SLR (MM)</b>	595	<b>ECE</b>	E4-106R-002395
<b>RC (MM)</b>	3940	<b>SRI</b>	625

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	2400	2850	3250	3700	4150	4450	5000	-	-
40	2400	2850	3250	3700	4150	4450	5000	-	-
30	2570	3050	3480	3960	4445	4765	5350	-	-
25	2665	3165	3610	4110	4610	4940	5550	-	-
10 CYC	2925	3600	4240	4875	5550	6040	6825	7200	7500
STATIC	4485	5520	6500	7475	8510	9260	10465	11040	11500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.