


# AGRIMAX SPARGO SB

<b>TIRE SIZE</b>	<b>VF 270/95 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR / SPRAYER
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	151 D



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	280	<b>RIM REC</b>	W9
<b>OD (MM)</b>	1491	<b>ECE</b>	E11-106R-0010500
<b>SLR (MM)</b>	692	<b>SRI</b>	725
<b>RC (MM)</b>	4546		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1480	1665	1855	2010	2230	2355	2575	2795	2985	3140
<b>FROM 65 TO 40</b>	1625	1830	2040	2210	2450	2590	2830	3075	3280	3450
30	1655	1870	2080	2255	2500	2640	2890	3135	3345	3520
20	1690	1905	2120	2300	2550	2695	2945	3200	3415	3590
10	1785	2015	2240	2430	2695	2850	3115	3380	3610	3795

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.