


# AW 09

|                           |   |
|---------------------------|---|
| <b>TIRE SIZE</b>          | <b>380/55 - 17</b>  |
| <b>UM</b>                 | IS STANDARD   |
| <b>CONSTRUCTION</b>       |  BIAS                      |
| <b>MACHINERY</b>          | PRESSE À PAILLE / OUTILLAGE<br>AGRICOLE / REMORQUE /<br>MOISSONNEUSE / OUTILLAGE<br>AGRICOLE / MOISSONNEUSE |
| <b>VERSION</b>            | STANDARD  |
| <b>TIRE TYPE</b>          | TL  |
| <b>LI/SS DRIVE WHEEL</b>  | 128 A8  |
| <b>LI/SS FREE ROLLING</b> | 141 A8  |



## DIMENSIONS IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 390  | <b>RIM REC</b> | 13.00          |
| <b>OD (MM)</b>  | 850  | <b>ECE</b>     | E4-106R-000380 |
| <b>SLR (MM)</b> | 377  |                |                |
| <b>RC (MM)</b>  | 2491 |                |                |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 3.20 |
|------------|------|
| 10 FR      | 3605 |
| 25 FR      | 3065 |
| 30 FR      | 2885 |
| 40 FR      | 2575 |
| 10 DW      | 2520 |
| 25 DW      | 2140 |
| 30 DW      | 2015 |
| 40 DW      | 1800 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.