

# AGRIMAX TURF RT 333

<b>TIRE SIZE</b>	<b>480/70 R 28</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	VINEYARD HARVESTER / ORCHARD HARVESTER / SMALL TRACTOR / TRACTOR / HARVESTER
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	140 A8 ; 140 B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	479	<b>RIM REC</b>	W 15 L
<b>OD (MM)</b>	1421	<b>RIM ALT</b>	W 14 L ; W 16 L
<b>SLR (MM)</b>	631	<b>ECE</b>	E11-106R-009049
<b>RC (MM)</b>	4228	<b>SRI</b>	675

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
50	1375	1600	1825	2050	2275	2500
40	1375	1600	1825	2050	2275	2500
30	1475	1715	1955	2195	2435	2675
10 LT	1845	2145	2450	2750	3050	3350
10 HT	1475	1715	1955	2195	2435	2675

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.