


# AW 711

<b>TIRE SIZE</b>	<b>VF 410/50 R 16.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ERNTMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE / ERNTMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	153 B



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	410	<b>RIM REC</b>	AG 13.00
<b>OD (MM)</b>	835	<b>ECE</b>	E11-106R-005024
<b>SLR (MM)</b>	350	<b>SRI</b>	400
<b>RC (MM)</b>	2513		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.6
<b>FROM 10 TO 50</b>	1025	1345	1630	1890	2175	2465	2655	2910	3195	3650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.