


AGRIMAX RT 765

TIRE SIZE	650/75 R 38
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SPRAYER / TRACTOR / VINEYARD HARVESTER / HARVESTER / IMPLEMENTS
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	169 D



DIMENSIONS US STANDARD

USA CODE	94063895	RC (IN)	229.1
SW (IN)	25.8	RIM REC	DW 21 B
OD (IN)	76.4	RIM ALT	DW 20 B; DW 23 B
SLR (IN)	34.4	ECE	E11-106R-006161

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	6020	6910	7940	8950	9980	11000	12030	12790
30	6320	7250	8330	9400	10480	11550	12620	13430
25	6590	7570	8700	9810	10930	12060	13170	14010
15	6910	7950	9130	10300	11470	12650	13820	14700
5 LT	8060	9260	10640	12000	13370	14750	16110	17140
5 HT	6910	7950	9130	10300	11470	12650	13820	14700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.