


# AGRIMAX V- FLECTO

<b>TIRE SIZE</b>	<b>VF 540/65 R 28</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HOCHLEISTUNGSTRAKTOR / TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	154 D



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94062126	<b>RC (IN)</b>	163.8
<b>SW (IN)</b>	21.6	<b>RIM REC</b>	DW 20 B
<b>OD (IN)</b>	55.6	<b>RIM ALT</b>	DW 18 L
<b>SLR (IN)</b>	24.5	<b>ECE</b>	E11-106R-005710

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
45	4210	4960	5630	6320	6910	7520
<b>FROM 40 TO 25</b>	4630	5460	6190	6940	7610	8270
20	4720	5560	6320	7080	7750	8430
12	4810	5670	6440	7220	7900	8600
5	5090	6000	6810	7640	8370	9090
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	6480	7640	8660	9720	10650	11570
5 HT	4720	5560	6320	7080	7750	8430

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.