


AGRIMAX SPARGO

TIRE SIZE	VF 480/80 R 42
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRATOR
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	176 D



DIMENSÕES IS STANDARD

SW (MM)	479	RIM REC	DW 16 L
OD (MM)	1835	RIM ALT	DW 15 L
SLR (MM)	838	ECE	E11-106R-009072
RC (MM)	5572	SRI	875

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.4	1.6	1.8	2	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6
70	3675	4070	4465	4660	4925	5055	5185	5450	5715	5910	6170	6370	6565
FROM 65 TO 40	3975	4405	4825	5040	5325	5470	5610	5890	6180	6390	6675	6890	7100
30	4055	4495	4925	5145	5435	5580	5725	6010	6305	6525	6810	7030	7245
20	4135	4580	5020	5245	5540	5690	5835	6130	6425	6650	6940	7165	7385
10*	4375	4845	5310	5545	5860	6015	6170	6480	6795	7030	7340	7575	7810
UPTO 30 CYCLIC	4515	5000	5480	5720	6045	6210	6370	6690	7015	7255	7575	7820	8060
UPTO 15 CYCLIC	5390	5970	6540	6830	7220	7410	7605	7985	8375	8665	9045	9335	9625
UPTO 10 CYCLIC	5965	6605	7240	7565	7995	8205	8415	8840	9270	9590	10015	10335	10655

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.