


# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>710/70 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ОПРЫСКИВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	175 D ; 178 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94063536	<b>RC (IN)</b>	226.4
<b>SW (IN)</b>	28.2	<b>RIM REC</b>	DW 23 B
<b>OD (IN)</b>	77.1	<b>ECE</b>	E11-106R-006000
<b>SLR (IN)</b>	33.8	<b>TRA CODE</b>	R1W

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	47
<b>40</b>	5940	7000	8070	8980	10040	10960	12030	12930	14150	15210
<b>30</b>	6240	7350	8470	9420	10550	11510	12620	13580	14860	15970
<b>25</b>	6450	7610	8760	9750	10910	11900	13060	14050	15380	16530
<b>20</b>	6820	8060	9280	10330	11550	12600	13820	14870	16270	17490
<b>5 LT</b>	7960	9380	10810	12040	13460	14680	16110	17340	18970	20390
<b>5 HT</b>	6820	8060	9280	10330	11550	12600	13820	14870	16270	17490

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.