

# PRO RIB F2M

|                     |                                       |
|---------------------|---------------------------------------|
| <b>TIRE SIZE</b>    | 11.00 - 16 SL                         |
| <b>UM</b>           | US STANDARD                           |
| <b>CONSTRUCTION</b> | ❖ BIAS                                |
| <b>MACHINERY</b>    | TRACTEUR 2WD / TRACTEUR /<br>REMORQUE |
| <b>VERSION</b>      | STANDARD                              |
| <b>TIRE TYPE</b>    | TL                                    |
| <b>LI/SS</b>        | 114 A8                                |



## DIMENSIONS US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>CODE USA</b> | 94027828 | <b>RC (IN)</b> | 111.4          |
| <b>SW (IN)</b>  | 13.2     | <b>RIM REC</b> | 10 LB          |
| <b>OD (IN)</b>  | 37.4     | <b>RIM ALT</b> | W 8 L; 8 LB    |
| <b>SLR (IN)</b> | 17.3     | <b>ECE</b>     | E4-106R-002667 |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>40</b> |
| 25               | 2060      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.