

FLOTATION 648

TIRE SIZE	750/60 - 30.5
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ПРЕСС-ПОДБОРЩИК / КОМБАЙН / РАЗБРАСЫВАТЕЛЬ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	170 A8/167 B
LI/SS FREE ROLLING	182 A8/179 B



РАЗМЕРЫ US STANDARD

USA CODE	94006540	RC (IN)	194.3
SW (IN)	29.7	RIM REC	AG 24.00
OD (IN)	65.9	ECE	E4-106R-001552
SLR (IN)	28.0	PR	16

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	26	29	32
5 FR	23330	24810	26230
10 FR	21000	22330	23610
20 FR	18660	19850	20990
25 FR	16670	17720	18740
30 FR	15000	15950	17080
5 DW	16470	17510	18520
10 DW	14810	15760	16670
20 DW	13170	14010	14810
25 DW	11760	12510	13230
30 DW	10580	11260	12010

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.