

# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>250/85 R 28</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	112 A8/B



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94047666	<b>RC (IN)</b>	134.7
<b>SW (IN)</b>	9.9	<b>RIM REC</b>	W 8
<b>OD (IN)</b>	44.8	<b>RIM ALT</b>	W 7; W 9
<b>SLR (IN)</b>	20.4	<b>ECE</b>	E4-106R-000646

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
<b>30</b>	1370	1590	1810	2030	2250	2470
<b>25</b>	1370	1590	1810	2030	2250	2470
<b>20</b>	1450	1700	1940	2170	2410	2650
<b>5 LT</b>	1830	2130	2420	2720	3020	3320
<b>5 HT</b>	1450	1700	1940	2170	2410	2650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.