

AS 509

TIRE SIZE	550/45 - 22.5
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	BALPRESS / ARBETSFORDON / SLÄPVAGN / SKÖRDEMASKIN / ARBETSFORDON
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	154 A8/150 B
LI/SS FREE ROLLING	166 A8/162 B



DIMENSIONER US STANDARD

USA CODE	94051038	RC (IN)	128.0
SW (IN)	21.3	RIM REC	AG 16.00
OD (IN)	41.9	ECE	E11-106R-004545
SLR (IN)	18.9	PR	20

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	44	51	58
5 FR	13820	15120	16360
10 FR	12440	13610	14730
20 FR	11070	12100	13080
25 FR	9880	10800	11680
30 FR	8880	9720	10470
5 SW	9790	10710	11570
10 DW	8810	9630	10420
20 DW	7830	8560	9260
25 DW	6990	7650	8270
30 DW	6290	6890	7390

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.