

AGRIMAX RT 855

TIRE SIZE	520/85 R 42
UM	IS STANDARD
MACHINERY	PULVÉRISATEUR / MACHINE À VENDANGER / TRACTEUR / MOISSONNEUSE / OUTILLAGE AGRICOLE
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	167 A8/B



DIMENSIONS IS STANDARD

SW (MM)	540	RIM REC	DW 16 L ; W 16 A ; DD 16
OD (MM)	1951	RIM ALT	DW 18 A ; DD 18 ; W 18 A ; DD 18 L
SLR (MM)	895	ECE	E4-106R-001491
RC (MM)	5919	SRI	925

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.4	2.8	3.2
50	2270	2640	3015	3385	3755	4125	4635	5070	5450
40	2270	2640	3015	3385	3755	4125	4635	5070	5450
30	2430	2830	3225	3625	4020	4415	4960	5425	5830
10 LT	3045	3540	4040	4535	5035	5530	6210	6795	7305
10 HT	2430	2830	3225	3625	4020	4415	4960	5425	5830

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.