

# AGRIMAX PROCROP

<b>TIRE SIZE</b>	<b>VF 270/95 R 48</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	SPRAYER
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	155 D



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	280	<b>RIM REC</b>	W9
<b>OD (MM)</b>	1745	<b>ECE</b>	E11-106R-0010174
<b>SLR (MM)</b>	815	<b>SRI</b>	850
<b>RC (MM)</b>	5330		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1660	1875	2085	2260	2510	2650	2895	3145	3355	3530
<b>FROM 65 TO 40</b>	1825	2055	2290	2480	2755	2910	3180	3450	3685	3875
30	1860	2100	2335	2535	2810	2970	3245	3520	3760	3955
20	1895	2140	2380	2580	2865	3025	3305	3590	3830	4030
10	2005	2265	2520	2730	3030	3200	3500	3800	4055	4265

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.