

# AGRIMAX RT 955

<b>TIRE SIZE</b>	<b>230/95 R 48</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	SPRAYER / VINEYARD HARVESTER / HARVESTER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	136 A8/B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94021864	<b>RC (IN)</b>	200.2
<b>SW (IN)</b>	9.0	<b>RIM REC</b>	W 7
<b>OD (IN)</b>	65.2	<b>RIM ALT</b>	W 8
<b>SLR (IN)</b>	31.2	<b>ECE</b>	E4-106R-000778

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	58	64
30	1930	2520	3060	3360	3560	3900	4250	4600	4930	-
25	1930	2520	3060	3360	3560	3900	4250	4600	4930	-
20	2070	2700	3280	3600	3810	4190	4550	4930	5290	-
5	2300	2900	3560	4230	4890	5040	5630	6230	6820	7410

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.