


AGRIMAX RT 855

| | |
|---------------------|--|
| TIRE SIZE | 420/80 R 46 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | IRRORAZIONE / VENDEMMIATRICE / TRATTORE / MIETITREBBIA / ATTREZZI AGRICOLI |
| VERSIONE | SPECIAL |
| TIRE TYPE | TL |
| LI/SS | 159 D ; 170 A2 |



DIMENSIONI US STANDARD

| | | | |
|-------------------|----------|----------------|----------------|
| CODICE USA | 94062065 | RC (IN) | 222.1 |
| SW (IN) | 16.5 | RIM REC | W 13 |
| OD (IN) | 72.4 | RIM ALT | W 12 |
| SLR (IN) | 34.0 | ECE | E4-106R-001489 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 | 41 | 46 |
|-----------|------|------|------|------|------|------|------|-------|-------|-------|
| 40 | 3580 | 4110 | 4720 | 5320 | 5940 | 6550 | 7080 | 7610 | 8970 | 9640 |
| 30 | 3760 | 4320 | 4960 | 5600 | 6240 | 6880 | 7440 | 7990 | 9420 | 10130 |
| 25 | 3920 | 4510 | 5170 | 5840 | 6500 | 7180 | 7760 | 8330 | 9830 | 10570 |
| 20 | 4120 | 4730 | 5430 | 6130 | 6830 | 7530 | 8150 | 8750 | 10330 | 11100 |
| 5 | 4930 | 5650 | 6490 | 7330 | 8170 | 9010 | 9740 | 10470 | 12300 | 13230 |
| 5 LT | 4790 | 5510 | 6330 | 7140 | 7960 | 8770 | 9490 | 10200 | 12030 | 12930 |
| 5 HT | 4120 | 4730 | 5430 | 6130 | 6830 | 7530 | 8150 | 8750 | 10330 | 11100 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.