


# CON STAR

<b>TIRE SIZE</b>	<b>480/80 - 26</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	КОМПАКТНЫЙ ПОГРУЗЧИК / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / КОМПАКТНЫЙ ПОГРУЗЧИК / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
<b>VERSION</b>	INDUSTRIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	160 A8



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	490	<b>RIM REC</b>	DW 15 L
<b>OD (MM)</b>	1410	<b>RIM ALT</b>	DW 16 L
<b>SLR (MM)</b>	643	<b>ECE</b>	E11-106R-003033
<b>RC (MM)</b>	4272	<b>SRI</b>	675

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>3.20</b>
40	4500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.