


RIDEMAX FROST

TIRE SIZE	440/80 R 24 IND
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTEUR
VERSION	STEEL BELTED
TIRE TYPE	TL
LI/SS	154 A8 ; 149 D



DIMENSIONS IS STANDARD

SW (MM)	441	RIM REC	DW 14 L
OD (MM)	1314	RIM ALT	DW 15 L
SLR (MM)	597	ECE	E11-106R-0011765
RC (MM)	3984	SRI	625

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2	2.4	2.6	2.8	3	3.2
65	1495	1920	2340	2570	2765	2895	3025	3155	3250
50	1615	2075	2530	2775	2985	3125	3265	3405	3510
40	1725	2210	2695	2955	3180	3330	3480	3630	3750
30	1795	2305	2810	3085	3315	3475	3630	3785	3900
20	1885	2420	2950	3240	3485	3645	3810	3975	4095
10	2155	2765	3370	3700	3980	4170	4355	4540	4680
5	2500	3205	3910	4290	4620	4835	5050	5270	5430

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.