

# AGRIMAX TERIS

<b>TIRE SIZE</b>	<b>IF 580/80 R 34 CFO</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	HARVESTER / COTTON PICKER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	177 D



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	586	<b>RIM REC</b>	DW 20 B; DW 20 A
<b>OD (MM)</b>	1792	<b>RIM ALT</b>	DW 21 A; DW 21 B
<b>SLR (MM)</b>	810	<b>ECE</b>	E4-106R-001833
<b>RC (MM)</b>	5422	<b>SRI</b>	850

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6
<b>70</b>	2460	2860	3260	3725	4120	4520	4985	5250	5785	6250	6645
<b>FROM 65 TO 40</b>	2705	3140	3580	4090	4530	4965	5405	5770	6355	6865	7300
<b>30</b>	2815	3270	3725	4225	4710	5165	5700	6005	6610	7140	7595
<b>20</b>	2920	3395	3865	4420	4890	5365	5915	6230	6860	7415	7885
<b>10</b>	3435	3990	4545	5195	5755	6310	6960	7330	8070	8720	9275
<b>UPTO 30 CYC*</b>	3515	4085	4655	5315	5885	6455	7210	7500	8260	8925	9490
<b>UPTO 15 CYC*</b>	4190	4870	5545	6340	7020	7695	8490	8940	9845	10640	11315
<b>10 HT</b>	2815	3270	3725	4225	4710	5165	5700	6005	6610	7140	7595

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.