


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>320/85 R 36</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZATOR / MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	128 A8/B



## DIMENSIUNI IS STANDARD

<b>SW (MM)</b>	329	<b>RIM REC</b>	W 11
<b>OD (MM)</b>	1458	<b>RIM ALT</b>	W 9; W 10
<b>SLR (MM)</b>	672	<b>ECE</b>	E4-106R-000762
<b>RC (MM)</b>	4404	<b>SRI</b>	700

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
50	990	1155	1315	1480	1640	1800
40	990	1155	1315	1480	1640	1800
30	1065	1240	1410	1585	1760	1930
10 LT	1330	1550	1765	1985	2200	2415
10 HT	1065	1240	1410	1585	1760	1930

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.