

# AGRIMAX V- FLECTO

**VF 600/65 R 28**

<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	YÜKSEK GÜÇTE TRAKTÖR / TRAKTÖR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	163 D



## UNDEFINED US STANDARD

<b>USA CODE</b>	94070930	<b>RC (IN)</b>	175.3
<b>SW (IN)</b>	23.5	<b>RIM REC</b>	DW 21 B
<b>OD (IN)</b>	58.7	<b>RIM ALT</b>	DW 20 B
<b>SLR (IN)</b>	25.8	<b>ECE</b>	E11-106R-007602

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	4990	5780	6560	7440	8130	8820	9790
<b>FROM 40 TO 25</b>	5490	6350	7210	8170	8930	9680	10750
20	5600	6480	7350	8340	9100	9880	10970
12	5710	6600	7500	8500	9280	10060	11180
5	6040	6990	7930	8990	9820	10650	11830
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	7680	8880	10090	11440	12490	13550	15050
5 HT	5600	6480	7350	8340	9100	9880	10970

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.