


# AGRIMAX RT 657

<b>TIRE SIZE</b>	<b>320/65 R 18</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VINEYARD HARVESTER / TRACTOR / HARVESTER
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	125 A8/B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94073252	<b>RC (IN)</b>	105.0
<b>SW (IN)</b>	12.2	<b>RIM REC</b>	W 10
<b>OD (IN)</b>	34.8	<b>RIM ALT</b>	W 9 ; W 11
<b>SLR (IN)</b>	15.7	<b>ECE</b>	E11-106R-008145

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	47
30	1200	1420	1640	1820	2040	2230	2660	2950	3320	3640
25	1200	1420	1640	1820	2040	2230	2660	2950	3320	3640
20	1290	1530	1760	1950	2190	2380	2850	3160	3560	3900
5 LT	1620	1910	2200	2450	2740	2990	3570	3960	4450	4880
5 HT	1290	1530	1760	1950	2190	2380	2850	3160	3560	3900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.