

MULTIMAX MP 522

TIRE SIZE	280/80 R 18 IND
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	COMPACT LOADER / TELEHANDLER / COMPACT LOADER / TELEHANDLER
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	132 A8/B



DIMENSIONS IS STANDARD

SW (MM)	282	RIM REC	W 9; 9; 9 SDC
OD (MM)	907	RIM ALT	W 8; W 10
SLR (MM)	421	ECE	E11-106R-002962
RC (MM)	2748	SRI	425

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	960	1140	1300	1480	1660	1780	2000	-	-
40	960	1140	1300	1480	1660	1780	2000	-	-
30	1030	1220	1395	1585	1780	1905	2140	-	-
25	1070	1270	1445	1645	1845	1980	2220	-	-
10 CYC.	1170	1440	1695	1950	2220	2415	2730	2880	3000
STATIC	1795	2210	2600	2990	3405	3705	4190	4420	4600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.