


# AGRIMAX V- FLECTO



<b>TIRE SIZE</b>	<b>VF 480/80 R 46</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRATTORE A ELEVATA POTENZA / TRATTORE
<b>VERSIONE</b>	STEEL BELTED SPL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	175 D

## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	479	<b>RIM REC</b>	DW 16 L
<b>OD (MM)</b>	1940	<b>RIM ALT</b>	DW 15 L
<b>SLR (MM)</b>	892	<b>ECE</b>	E11-106R-0010596
<b>RC (MM)</b>	5855	<b>SRI</b>	925

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
70	2450	2890	3330	3710	4145	4525	4965	5340	5845	6280
FROM 65 TO 40	2695	3175	3660	4075	4555	4970	5455	5865	6420	6900
30	2750	3240	3735	4155	4650	5070	5565	5985	6550	7040
20	2805	3305	3810	4240	4740	5170	5675	6105	6680	7180
10	2965	3495	4025	4480	5010	5465	6000	6455	7060	7590
UPTO 30 CYC	3060	3605	4155	4625	5175	5645	6190	6660	7290	7835
UPTO 15 CYC	3650	4305	4960	5520	6175	6735	7390	7950	8700	9350
UPTO 10 CYC	4000	4715	5435	6050	6765	7380	8100	8715	9535	10250
10HT	2750	3240	3735	4155	4650	5070	5565	5985	6550	7040

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.