


# AGRIMAX SIRIO

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>540/65 R 30</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRACTOR DE ALTA POTENCIA / TRACTOR   |
| <b>VERSIÓN</b>      | HIGH SPEED   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 150 D ; 147 E  |



## DIMENSIONES US STANDARD

|                   |          |                |                |
|-------------------|----------|----------------|----------------|
| <b>CÓDIGO USA</b> | 94045310 | <b>RC (IN)</b> | 173.2          |
| <b>SW (IN)</b>    | 20.9     | <b>RIM REC</b> | W 16 L         |
| <b>OD (IN)</b>    | 57.6     | <b>RIM ALT</b> | W 18           |
| <b>SLR (IN)</b>   | 26.3     | <b>ECE</b>     | E4-106R-000814 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9    | 12   | 15   | 17   | 20   | 23   | 29    | 35    |
|-----------|------|------|------|------|------|------|-------|-------|
| 45        | 3200 | 3670 | 4210 | 4750 | 5290 | 5830 | 6300  | 6780  |
| 40        | 3470 | 3990 | 4590 | 5170 | 5760 | 6360 | 6880  | 7390  |
| 30        | 3650 | 4200 | 4820 | 5430 | 6060 | 6680 | 7220  | 7760  |
| 25        | 3800 | 4380 | 5030 | 5670 | 6320 | 6970 | 7530  | 8090  |
| 15        | 4120 | 4730 | 5430 | 6130 | 6830 | 7530 | 8150  | 8750  |
| 5         | 5210 | 5990 | 6880 | 7760 | 8640 | 9530 | 10310 | 11080 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.