


# AGRIMAX RT 955

<b>TIRE SIZE</b>	<b>230/95 R 36</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	130 A8/B



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94027477	<b>RC (IN)</b>	161.9
<b>SW (IN)</b>	9.0	<b>RIM REC</b>	W 7
<b>OD (IN)</b>	53.2	<b>RIM ALT</b>	W 8
<b>SLR (IN)</b>	25.2	<b>ECE</b>	E4-106R-000765

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	58	64
30	1640	2140	2600	2850	3020	3320	3600	3900	4180	-
25	1640	2140	2600	2850	3020	3320	3600	3900	4180	-
20	1750	2290	2790	3050	3240	3550	3870	4180	4490	-
5	1950	2460	3020	3580	4160	4280	4780	5280	5790	6280

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.