


AGRIMAX FORTIS

TIRE SIZE	710/75 R 42
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	175 D ; 172 E



ABMESSUNGEN IS STANDARD

SW (MM)	716	RIM REC	DW 23 B
OD (MM)	2133	RIM ALT	DW 25 B
SLR (MM)	970	ECE	E4-106R-001835
RC (MM)	6406	SRI	1000

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	3025	3530	3970	4410	4855	5230	5800	6300
65	3315	3865	4350	4830	5315	5730	6350	6900
50	3480	4060	4565	5075	5580	6015	6670	7245
40	3630	4235	4765	5295	5825	6275	6960	7560
30	3810	4445	5000	5555	6110	6590	7305	7935
10 LT	4440	5180	5830	6475	7125	7680	8510	9250
10 HT	3810	4445	5000	5555	6110	6590	7305	7935

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.