

XL GRIP (SCRAPER)



XL GRIP (SCRAPER)

XL GRIP (SCRAPER) is a non-directional wide-base tyre, particularly suitable for scrapers on any terrain. The tyre features a strong casing and a special tread compound providing high cut and puncture resistance as well as excellent durability and traction even during heavy-duty operations. Additional features are best self-cleaning properties and exceptional stability.



	SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø29"	33.25 - 29	TL	E3	32	-	27.00/3.5	26.00/3.5	0	862	2120	0	0	46	STD
	29.5 - 29	TL	E3	28	-	25.00/3.5	26.00/3.5	0	760	1965	0	0	39	STD
Ø35"	33.25 - 35	TL	E3	32	-	27.00/3.5	29.00/3.5	0	862	2270	0	0	46	STD
	33.25 - 35	TL	E3	38	-	27.00/3.5	29.00/3.5	0	862	2270	0	0	46	STD

STD: STANDARD

TECHNOLOGIES	PERFORMANCES
   	    

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

	SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH (TK/H)	OW (MM)	OD	SLR	RC	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM		(mm)	(mm)	(mm)	(mm)		
														
	37.25 - 35	TL	E3	36	-	31.00/4.0	29.00/3.5	0	955	2364	0	0	52	STD
Ø39"	37.5 - 39	TL	E3	52	-	32.00/4.5	-	0	975	2570	0	0	52	STD

STD: STANDARD



TECHNOLOGIES		PERFORMANCES	
			
			

Permissible tolerances: O.O. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB - 23/09/2026