


AGRIMAX SPARGO

| | |
|--------------|--|
| TIRE SIZE | VF 480/95 R 50 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 181 D |



DIMENSIONI IS STANDARD

| | | | |
|----------|------|---------|------------------|
| SW (MM) | 479 | RIM REC | DW 16 L |
| OD (MM) | 2182 | RIM ALT | DW 15 L |
| SLR (MM) | 991 | ECE | E11-106R-0010083 |
| RC (MM) | 6606 | SRI | 1025 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.0 | 1.2 | 1.4 | 1.6 | 1.8 | 2.0 | 2.2 | 2.4 | 2.6 | 2.8 | 3.0 | 3.2 |
|---------------|------|------|------|------|------|------|------|------|------|------|------|------|
| 70 | 4045 | 4500 | 5035 | 5495 | 5800 | 6025 | 6255 | 6485 | 6790 | 7095 | 7325 | 7630 |
| FROM 65 TO 40 | 4375 | 4865 | 5445 | 5940 | 6270 | 6515 | 6765 | 7015 | 7345 | 7675 | 7920 | 8250 |
| 30 | 4460 | 4960 | 5550 | 6060 | 6400 | 6645 | 6900 | 7155 | 7490 | 7825 | 8080 | 8415 |
| 20 | 4550 | 5060 | 5660 | 6180 | 6525 | 6775 | 7035 | 7295 | 7635 | 7980 | 8240 | 8580 |
| 10 | 4810 | 5350 | 5985 | 6535 | 6900 | 7165 | 7440 | 7715 | 8075 | 8440 | 8715 | 9075 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.