

AGRIMAX V- FLECTO

VF 650/65 R 34 NRO

UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	YÜKSEK GÜÇTE TRAKTÖR / TRAKTÖR
VERSION	STANDARD
TIRE TYPE	TL
	170 D



UNDEFINED IS STANDARD

SW (MM)	650	RIM REC	DW 23 B
OD (MM)	1710	RIM ALT	DW 21 B
SLR (MM)	756	ECE	E11-106R-008812
RC (MM)	5110	SRI	825

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	2780	3220	3655	4145	4530	5075	5460
FROM 65 TO 40	3060	3540	4020	4560	4980	5580	6000
30	3120	3610	4100	4650	5075	5690	6120
20	3180	3680	4180	4740	5175	5800	6240
10	3365	3890	4420	5015	5475	6135	6600
*UPTO 10 CYC WITH FRONT LOADER	4280	4955	5625	6380	6970	7810	8400
10 HT	3120	3610	4100	4650	5075	5690	6120

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.