


FL 630 ULTRA

TIRE SIZE	600/55 R 26.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SPRIDARE / TANKBIL / SLÄPVAGN / ARBETSFORDON
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	165 D ; 176 A8



DIMENSIONER IS STANDARD

SW (MM)	611	RIM REC	AG 20.00
OD (MM)	1333	ECE	E11-106R-006813
SLR (MM)	579	SRI	625
RC (MM)	4070		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
65	1650	1910	2165	2630	3040	3505	3970	4275	4740	5150
50	2000	2310	2620	3180	3680	4240	4805	5180	5740	6235
40	2275	2630	2985	3625	4190	4830	5470	5895	6535	7100
25	2605	3015	3420	4155	4805	5540	6270	6760	7490	8140
10	2970	3435	3895	4730	5470	6305	7140	7695	8530	9270

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.