



## DATA SHEET

Última  
actualización  
10-07-2026

# TR 135

|                  |                    |
|------------------|--------------------|
| <b>TIRE SIZE</b> | <b>8.3 - 28</b>    |
| <b>UM</b>        | US STANDARD        |
| <b>MACHINERY</b> | TRACTOR / REMOLQUE |
| <b>VERSIÓN</b>   | STANDARD           |
| <b>TIRE TYPE</b> | TT                 |
| <b>LI/SS</b>     | 99 A8              |



### DIMENSIONES US STANDARD

|                   |          |                |                |
|-------------------|----------|----------------|----------------|
| <b>CÓDIGO USA</b> | 94004607 | <b>RC (IN)</b> | 131.8          |
| <b>SW (IN)</b>    | 8.4      | <b>RIM REC</b> | W 7            |
| <b>OD (IN)</b>    | 43.5     | <b>RIM ALT</b> | W 6            |
| <b>SLR (IN)</b>   | 20.4     | <b>ECE</b>     | E4-106R-001973 |

### LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>36</b> |
| 25               | 1710      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.