

AGRIMAX RT 765

| | |
|---------------------|--|
| TIRE SIZE | 600/70 R 30 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ОПРЫСКИВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 152 D |



РАЗМЕРЫ IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 611 | RIM REC | DW 20 B |
| OD (MM) | 1602 | RIM ALT | DW 18 L; W 18 L |
| SLR (MM) | 711 | ECE | E11-106R-005523 |
| RC (MM) | 4774 | SRI | 750 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|------------|------|------|------|------|------|------|
| 65 | 1955 | 2275 | 2595 | 2915 | 3235 | 3550 |
| 50 | 2055 | 2390 | 2725 | 3060 | 3395 | 3730 |
| 40 | 2140 | 2490 | 2840 | 3190 | 3540 | 3890 |
| 30 | 2250 | 2615 | 2985 | 3350 | 3720 | 4085 |
| 10 LT | 2620 | 3050 | 3475 | 3905 | 4335 | 4760 |
| 10 HT | 2250 | 2615 | 2985 | 3350 | 3720 | 4085 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.