

# AGRIMAX V- FLECTO

**VF 710/70 R 38**

<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	YÜKSEK GÜÇTE TRAKTÖR / TRAKTÖR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	181 D



## UNDEFINED US STANDARD

<b>USA CODE</b>	94063710	<b>RC (IN)</b>	227.3
<b>SW (IN)</b>	28.1	<b>RIM REC</b>	DW 24 B
<b>OD (IN)</b>	77.2	<b>RIM ALT</b>	DW 23 B; DW 25 B
<b>SLR (IN)</b>	33.2	<b>ECE</b>	E11-106R-006163

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	8270	9590	10910	12400	13720	15050	16540
<b>FROM 40 TO 25</b>	9090	10550	12000	13630	15090	16540	18190
20	9270	10760	12230	13900	15390	16880	18550
12	9460	10970	12480	14170	15690	17210	18910
5	10000	11600	13190	14990	16590	18200	20010
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	12730	14760	16800	19080	21120	23160	25460
5 HT	9270	10760	12230	13900	15390	16880	18550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.