



US standard



GROWING TOGETHER

IT 400



PRODUCT DATA SHEET



Bias



IT 400

IT 400 is a road-oriented rib-pattern tire for low platforms in transport applications. The tire is suitable for high-speed applications and provides significant fuel savings.

Technologies



High Speed

Performance



Fuel Economy



Road Oriented

| | US CODE | Tire size | Type | PR | LI/SS | Version | O.D. (In.) | S.W. (In.) | SLR (In.) | RC (In.) | TREAD DEPTH (32nds) | TIRE WEIGHT (lbs) | RIM | |
|--------------|----------|------------|------|----|-----------|---------|---------------|---------------|--------------|-------------|---------------------------|-------------------------|------|-----------------|
| | | | | | | | | | | | | | Rec. | Alt. |
| Ø 15" | 94008278 | 7.50 - 15 | TT | 16 | 125/121 J | STD | 31.3 | 8.3 | 14.0 | 93.0 | 15 | 47 | 6.0 | 5.50 F; 6.50 |
| | 94008292 | 8.25 - 15 | TT | 14 | 129/125 J | STD | 33.3 | 9.4 | 14.8 | 98.9 | 16 | 58 | 6.50 | 6.0; 7.0 |
| | 94031818 | 8.25 - 15 | TL | 14 | 129/125 J | STD | 33.3 | 9.4 | 14.8 | 98.9 | 16 | 61 | 6.50 | 6.0; 7.0 |
| | 94029020 | 8.25 - 15 | TT | 16 | 131/126 J | STD | 33.3 | 9.4 | 14.8 | 98.9 | 16 | 58 | 6.50 | 6.0; 7.0 |
| | 94008230 | 10.00 - 15 | TT | 14 | 137/133 J | STD | 36.4 | 10.8 | 16.1 | 108.1 | 18 | 71 | 7.5 | 7.0; 8.0 |
| | 94008254 | 10.00 - 15 | TT | 16 | 141/136 J | STD | 36.4 | 10.8 | 16.1 | 108.1 | 18 | 71 | 7.5 | 7.0; 8.0 |
| | 94008261 | 10.00 - 15 | TT | 18 | 143/138 J | STD | 36.4 | 10.8 | 16.1 | 108.1 | 18 | 73 | 7.5 | 7.0; 8.0 |

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference