

# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>210/90 R 20</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	IRRORAZIONE / VENDEMMIATRICE / TRATTORE / MIETITREBBIA / ATTREZZI AGRICOLI
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	110 A8/B



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	211	<b>RIM REC</b>	W 7
<b>OD (MM)</b>	890	<b>RIM ALT</b>	W 6
<b>SLR (MM)</b>	412	<b>ECE</b>	E4-106R-001817
<b>RC (MM)</b>	2681	<b>SRI</b>	425

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
<b>50</b>	500	575	660	745	830	915	990	1060
<b>40</b>	500	575	660	745	830	915	990	1060
<b>30</b>	535	615	705	795	890	980	1060	1135
<b>10 LT</b>	670	770	885	1000	1115	1230	1330	1425
<b>10 HT</b>	535	615	705	795	890	980	1060	1135

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.