


AGRIMAX FORCE

| | |
|---------------------|--|
| TIRE SIZE | IF 420/85 R 38 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | MIETITREBBIA / TRATTORE A ELEVATA POTENZA / TRATTORE |
| VERSIONE | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 155 D |



DIMENSIONI US STANDARD

| | | | |
|-------------------|----------|----------------|-----------------|
| CODICE USA | 94058044 | RC (IN) | 197.5 |
| SW (IN) | 16.5 | RIM REC | DW 14 L |
| OD (IN) | 65.7 | RIM ALT | DW 15 L |
| SLR (IN) | 30.7 | ECE | E11-106R-004897 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|--------------------------------------|------|------|------|------|------|-------|-------|-------|
| 45 | 3650 | 4190 | 4810 | 5430 | 6050 | 6680 | 7300 | 7770 |
| FROM 40 TO 25 | 4010 | 4610 | 5290 | 5970 | 6660 | 7340 | 8020 | 8550 |
| 20 | 4170 | 4780 | 5500 | 6210 | 6920 | 7630 | 8340 | 8880 |
| 12 | 4330 | 4970 | 5710 | 6450 | 7190 | 7930 | 8660 | 9230 |
| 5 | 5090 | 5840 | 6710 | 7580 | 8450 | 9310 | 10180 | 10850 |
| *UPTO 5 CYC WITH FRONT LOADER | 5610 | 6450 | 7410 | 8360 | 9310 | 10270 | 11230 | 11960 |
| 5 HT | 4170 | 4780 | 5500 | 6210 | 6920 | 7630 | 8340 | 8880 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.