


# RM 500

<b>TIRE SIZE</b>	<b>500/85 R 24</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MIETITREBBIA
<b>VERSIONE</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	182 A8 ; 170 A8



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	520	<b>RIM REC</b>	W 16 L
<b>OD (MM)</b>	1460	<b>RIM ALT</b>	W 15 L
<b>SLR (MM)</b>	622	<b>ECE</b>	E11-106R-005991
<b>RC (MM)</b>	4382	<b>SRI</b>	700

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
<b>40 FREE ROLLING</b>	3570	4335	5015	5780	6545	7055	7735	8500
<b>40 DRIVE WHEEL</b>	2520	3060	3540	4080	4620	4980	5460	6000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.