


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>520/85 R 42</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SPRAYER / VINEYARD HARVESTER / TRACTOR / HARVESTER / IMPLEMENTS
<b>VERSION</b>	SPECIAL
<b>TL/TT</b>	TL
<b>LI/SS</b>	167 A8/B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94060139	<b>RC (IN)</b>	227.6
<b>SW (IN)</b>	20.3	<b>RIM REC</b>	DW 16 L ; W 16 A ; DD 16
<b>OD (IN)</b>	76.8	<b>RIM ALT</b>	DW 18 A ; DD 18 ; W 18 A ; DD 18 L
<b>SLR (IN)</b>	33.8	<b>ECE</b>	E4-106R-001491

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	35	41	46
30	5000	5820	6650	7460	8280	9090	10220	11180	12010
25	5000	5820	6650	7460	8280	9090	10220	11180	12010
20	5360	6240	7110	7990	8860	9730	10930	11960	12850
5 LT	6710	7800	8910	10000	11100	12190	13690	14980	16100
5 HT	5360	6240	7110	7990	8860	9730	10930	11960	12850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.