


MULTIMAX MP 527

TIRE SIZE	400/80 R 24 IND
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	CARREGADORA COMPACTA / LEVANTADOR TELESCÓPICO / CARREGADORA COMPACTA / LEVANTADOR TELESCÓPICO
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	162 A8/B



DIMENSÕES US STANDARD

CÓDIGO USA	94052226	RC (IN)	150.9
SW (IN)	15.9	RIM REC	DW 13
OD (IN)	49.2	RIM ALT	DW 12 ; DW 13 L ; DW 14 L
SLR (IN)	22.8	ECE	E11-106R-002982

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	23	29	35	41	46	49	52	58	64	67	70	73	75	78
30	4090	4820	5650	6390	7120	7390	7760	8590	9300	9780	10010	10470	-	-
25	4090	4820	5650	6390	7120	7390	7760	8590	9300	9780	10010	10470	-	-
20	4380	5160	6060	6840	7630	7910	8310	9190	9950	10460	10710	11210	-	-
15	4540	5360	6280	7100	7910	8210	8620	9550	10340	10860	11110	11630	-	-
5 CYC.	5030	6140	7230	8490	9590	10140	10680	11640	12890	13430	13950	14670	15010	15710
STATIC	7720	9410	11090	13010	14700	15540	16380	17860	19750	20590	21410	22500	23030	24080

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.