


AGRIMAX V- FLECTO

| | |
|---------------------|--|
| TIRE SIZE | VF 340/85 R 28 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTEUR DE FORTE PUISSANCE / TRACTEUR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 139 D |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|------------------|
| SW (MM) | 355 | RIM REC | W 12 |
| OD (MM) | 1290 | RIM ALT | W 11 |
| SLR (MM) | 571 | ECE | E11-106R-0010342 |
| RC (MM) | 3833 | SRI | 625 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1 | 1.2 | 1.4 | 1.6 |
|---------------------------------------|------------|------------|----------|------------|------------|------------|
| 70 | 1215 | 1410 | 1610 | 1810 | 2010 | 2210 |
| FROM 65 TO 40 | 1335 | 1555 | 1770 | 1990 | 2210 | 2430 |
| 30 | 1360 | 1580 | 1805 | 2025 | 2250 | 2475 |
| 20 | 1385 | 1615 | 1840 | 2070 | 2295 | 2525 |
| 10 | 1600 | 2135 | 2670 | 3200 | 2425 | 2670 |
| *UPTO 10 CYC WITH FRONT LOADER | 1870 | 2175 | 2480 | 2785 | 3090 | 3400 |
| 10HT | 1360 | 1580 | 1805 | 2025 | 2250 | 2475 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.