

AGRIMAX RT 765M

| | |
|---------------------|---|
| TIRE SIZE | 710/70 R 42 |
| UM | IS STANDARD |
| CONSTRUCTION | |
| MACHINERY | SPRAYER / TRACTOR / VINEYARD HARVESTER / HARVESTER / IMPLEMENTS |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 173 D ; 176 A8 |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 716 | RIM REC | DW 23 B |
| OD (MM) | 2061 | RIM ALT | DW 25 B |
| SLR (MM) | 922 | ECE | E11-106R-006018 |
| RC (MM) | 6174 | SRI | 975 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|------------|------|------|------|------|------|------|------|------|
| 65 | 3055 | 3510 | 4030 | 4550 | 5070 | 5590 | 6110 | 6500 |
| 50 | 3210 | 3690 | 4235 | 4780 | 5325 | 5870 | 6420 | 6825 |
| 40 | 3350 | 3845 | 4415 | 4985 | 5555 | 6125 | 6695 | 7120 |
| 30 | 3515 | 4040 | 4635 | 5235 | 5835 | 6430 | 7030 | 7475 |
| 10 LT | 4095 | 4705 | 5405 | 6100 | 6795 | 7495 | 8190 | 8710 |
| 10 HT | 3515 | 4040 | 4635 | 5235 | 5835 | 6430 | 7030 | 7475 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.