


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>460/85 R 34</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	FELDSPRITZE / TRAUBENERNTEMASCHINE / TRACTOR / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	158 A8/B



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94047772	<b>RC (IN)</b>	191.5
<b>SW (IN)</b>	18.7	<b>RIM REC</b>	W 16 L
<b>OD (IN)</b>	64.8	<b>RIM ALT</b>	W 14 L ; W 15 L
<b>SLR (IN)</b>	28.4	<b>ECE</b>	E11-106R-006759

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46
<b>30</b>	3660	4310	4970	5530	6180	6750	7410	7970	8720	9370
<b>25</b>	3660	4310	4970	5530	6180	6750	7410	7970	8720	9370
<b>20</b>	3910	4620	5320	5920	6620	7230	7930	8530	9340	10030
<b>5 LT</b>	4910	5780	6660	7420	8290	9050	9920	10680	11680	12550
<b>5 HT</b>	4190	4950	5700	6340	7090	7740	8490	9130	9990	10740

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.