

AS 504

TIRE SIZE	12.5/80 - 18
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS DRIVE WHEEL	129 A8
LI/SS FREE ROLLING	142 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	308	RIM REC	W 9
OD (MM)	987	RIM ALT	9; 11
SLR (MM)	438	ECE	E11-106R-004346
RC (MM)	2892	PR	12

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.70
10 FR	3710
25 FR	3155
30 FR	2970
40 FR	2650
10 DW	2590
25 DW	2200
30 DW	2070
40 DW	1850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.