


# AGRIMAX RT 657

<b>TIRE SIZE</b>	<b>340/65 R 20</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRAKTOR / SKÖRDEMASKIN FÖR VINGÅRD / SKÖRDEMASKIN
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	124 D ; 127 A8



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	343	<b>RIM REC</b>	W 11
<b>OD (MM)</b>	950	<b>RIM ALT</b>	W 10 ; W 12
<b>SLR (MM)</b>	430	<b>ECE</b>	E4-106R-001413
<b>RC (MM)</b>	2892	<b>SRI</b>	450

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
<b>65</b>	755	880	1010	1120	1235	1330	1475	1600
<b>50</b>	790	925	1060	1180	1295	1395	1550	1680
<b>40</b>	825	965	1105	1225	1350	1455	1610	1750
<b>30</b>	865	1015	1160	1290	1420	1530	1695	1840
<b>10 LT</b>	1010	1180	1355	1505	1655	1785	1975	2145
<b>10 HT</b>	865	1015	1160	1290	1420	1530	1695	1840

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.