

AGRIMAX RT 657

TIRE SIZE	650/65 R 42
UM	IS STANDARD
MACHINERY	TRAUBENERNTEMASCHINE / TRACTOR / ERNTEMASCHINE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	165 D ; 168 A8

ABMESSUNGEN IS STANDARD

SW (MM)	645	RIM REC	DW 20 B
OD (MM)	1913	RIM ALT	DW 21 B ; DW 23 B
SLR (MM)	878	ECE	E4-106R-000625
RC (MM)	5810	SRI	925

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	2475	2885	3245	3605	3970	4275	4740	5150
50	2600	3030	3410	3790	4170	4495	4980	5410
40	2690	3140	3530	3920	4315	4650	5155	5600
30	2845	3320	3735	4150	4565	4920	5455	5925
10 LT	3315	3870	4355	4835	5320	5735	6355	6905
10 HT	2845	3320	3735	4150	4565	4920	5455	5925

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

