


# AGRIMAX V-FLECTO

<b>TIRE SIZE</b>	<b>VF 710/60 R 46</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	174 D



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94514168	<b>RC (IN)</b>	239.8
<b>SW (IN)</b>	28.1	<b>RIM REC</b>	DW 25 B
<b>OD (IN)</b>	80.4	<b>RIM ALT</b>	DW 27 B
<b>SLR (IN)</b>	35.3	<b>ECE</b>	E11-106R-0010941

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
45	7400	8610	9820	11030	12250	13450
<b>FROM 40 TO 25</b>	8120	9460	10790	12110	13450	14770
20	8290	9640	11000	12360	13710	15070
12	8450	9840	11220	12610	13990	15370
5	8940	10410	11870	13330	14790	16250
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	11380	13240	15100	16960	18830	20680
5 HT	8290	9640	11000	12360	13710	15070

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.